

DT2210

DT2210

Product ref: DT2210, DT2210 FI

DMX and RDM splitter/booster, 2 inputs to 10 outputs



The DT2210 is a 19" rackmount DMX splitter supporting Remote Device Management (RDM).

The DT2210 is used in larger DMX networks where more than simple daisy-chain connections between multiple DMX devices (to a maximum of 32 devices) are needed. DT2210 splitter (hub) boosts the signal to create a 'star' network of 10 additional DMX lines from a choice of two DMX inputs.

Outputs are grouped in pairs that can be selected to input A or B by pressing the adjacent panel push button. A fully galvanic-isolated version (FI) is also available.

Features include:

- 2 DMX inputs each with DMX thru (parallel) to 5 pairs DMX outputs selectable to A or B inputs (10 outputs total)
- Bi-directional Remote Device Management (RDM) compatible
- 19" rack mounted

- All DMX/RDM outputs are boosted signals (connect up to 32 devices per output)
- Optocoupler isolation for inputs, full isolation available as option (FI option)
- Bi-color LEDs confirm presence of viable DMX signal for inputs A and B
- USB connection for firmware updates

Dimensions	19" x 1U x 6.3in, 2.5kg [box size: 570 x 280 x 72, 6.4lbs gross]
Power	100-240VAC 50/60Hz, fixed mains cord
Connections	2 x XLR5 (M) DMX-In, 2 x XLR5 (F) DMX-Thru (paralleled), 10 x boosted XLR5 (F) DMX-out, USB
Options	Connections options: 3-pin or 5-pin, M or F XLR to special order
Supplied	DT2210, fitted mains cord, operator leaflet
Versions	DT2210: DMX/RDM splitter 2 inputs to 10 outputs, XLR5 DT2210 FI: DMX/RDM splitter 2 inputs to 10 outputs, Full galvanic isolation
Related products	DT125 range: DMX / RDM splitter 1 input to 5 outputs, truss/desk mounted DT229: DMX / RDM splitter 2 inputs to 9 outputs, 19" rack mounted